
Product data sheet

FLEX50
FX50H-598301-HXXXM
EGLO




pendant mounted direct LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 7 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 8 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 9 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Light output 10 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.44 W	CRI	80
Total flux	524 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	4.44 W

Mounting mode

Pendant

Shape and measurements

Length: 60.83 in

Width: 60.83 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 44.4 W

Protection

IP: 20

Designation labels: CE