Product data sheet

EP 145 LED 24L35 BP NR 730 RS/MTP F5M 96269230

THORN LIGHTING





A 19th Century styled post top lantern with 24 LEDs driven at 350mA with Narrow Road optic. Integral power reduction function which dims down to 50% power, effective 3 hours before and 5 hours after a calculated midnight. Class II electrical, IP66, IK08. Body: stainless steel, painted black (close to RAL9005). Canopy: GRP/Polyester, black (close to RAL9005) finish. Enclosure: 5mm thick tempered glass. Pre-wired with 5m H07-RNF cable. Complete with 3000K LED Dimensions: 420 x 420 x 767 mm Total power: 26 W Weight: 8.6 kg Scx: 0.145 m²

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	26 W	CRI	70
Total flux	2087 lm	LOR	100%
Luminous efficacy	80 lm/W	Total power	26 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 16.54 in Width: 16.54 in Height: 30.20 in Weight: 8.6 kg

Design

Material impression: Stainless steel Color of housing: Black

Electric

System power: 26 W Voltage: 230 V AC Appliance Class: II

Protection

IP: 66 IK: 08 Designation labels: CE