
Product data sheet


TRIONA OPAL
312383.002.1.76
RZB



IP 20 IK 03

Series: Triona Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Halterung, rückseitige Abdeckung und Leuchtenrahmen Metall pulverbeschichtet. Diffusor aus Kunststoff (PMMA) opal. Betriebsgerät eingebaut. Leuchtmittel (LED) im Lieferumfang enthalten. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 681, H 88 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3500lm System power: 33W Beam Angle: 104° Number of fittings B10A: 8 Number of fittings B16A: 13 Inrush current: 53A Unified Glare Ratio: 20,3 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	32.9 W	CRI	80
Total flux	3500 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	32.9 W

Mounting mode

Wall mounted

Shape and measurements

Height: 2.05 in
Diameter: 26.81 in

Adjustability

Fixed

Electric

System power: 32.9 W

Protection

IP: 20
IK: 03