




Product data sheet

BAYMASTER LED 15000 LUMENS WIDE OPTICS 3000K CCT DIFFUSED POLYCARBONATE I/BLLPL7WDW
 APPLETON (EMERSON EGS)



BAYMASTER LED Gen2 Highbay Series Pendant/Ceiling Mount 15000 LUMENS, 3000 K CCT Yoke Mount BU-120-277 Vac, 50/60Hz, BH-347-480 Vac , 50/60Hz 3/4" NPT Hub WIDE OPTICS DIFFUSED POLYCARBONATE Class I, Division 2, Groups A, B, C, D Class I, Zone 2 GROUP IIC Class II, Division 1&2, Group E, F, G Class III TYPE 3R, 4, 4X IP66/67 Suitable for Use in Wet Locations Marine Outside (Salt Water) Refer to catalog for additional options

Light output 1



1 x LED

Nominal lamp power	111 W	LOR	100%
Lamp flux	8686 lm	Total flux	8686 lm
Luminous efficacy	78 lm/W	Total power	111 W
CCT	3114 K		
CRI	83		

Mounting mode

Pendant

Shape and measurements

Length: 6.00 in

Width: 6.00 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 111 W

Appliance Class: II

Protection

IP: 67

IK: 06

Explosion zone suitability: 2