Product data sheet


GATU 21-001S-10GHV/M/940, S
21-001S-10GHV/M/940
HALLA



IP 20


21-001S-10GHV/M/940, S Luminaire recessed Material of luminaire: Colour of luminaire: Shape of luminaire: Angular Size: 185 x 185 x 100 mm Type of installation: Recessed Distribution: Direct Optics type: Reflector Protection class: II Voltage: 220-240V

Light output 1




1 x LED

Nominal lamp power	9.6 W	LOR	100%
Lamp flux	1110 lm	Total flux	1110 lm
Luminous efficacy	116 lm/W	Total power	9.6 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	24.5 W	LOR	100%
Lamp flux	2380 lm	Total flux	2380 lm
Luminous efficacy	97 lm/W	Total power	24.5 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	22.2 W	LOR	100%
Lamp flux	2220 lm	Total flux	2220 lm
Luminous efficacy	100 lm/W	Total power	22.2 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	20.1 W	LOR	100%
Lamp flux	2050 lm	Total flux	2050 lm
Luminous efficacy	102 lm/W	Total power	20.1 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1880 lm	Total flux	1880 lm
Luminous efficacy	104 lm/W	Total power	18 W
CCT	4000 K		
CRI	90		




1 x LED

Nominal lamp power	15.9 W	LOR	100%
Lamp flux	1700 lm	Total flux	1700 lm
Luminous efficacy	107 lm/W	Total power	15.9 W
CCT	4000 K		
CRI	90		



1 x LED


Nominal lamp power	13.8 W	LOR	100%
Lamp flux	1510 lm	Total flux	1510 lm
Luminous efficacy	109 lm/W	Total power	13.8 W
CCT	4000 K		
CRI	90		



1 x LED

Nominal lamp power	11.8 W	LOR	100%
Lamp flux	1310 lm	Total flux	1310 lm
Luminous efficacy	111 lm/W	Total power	11.8 W
CCT	4000 K		
CRI	90		

Light output 2 (emergency)



1 x LED

Nominal lamp power	1.5 W	LOR	100%
Lamp flux	220 lm	Total flux	220 lm
Luminous efficacy	147 lm/W	Total power	1.5 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.28 in
Width: 7.28 in
Height: 3.35 in

Adjustability

Tiltable

Electric

System power: 11.1-26 W
Appliance Class: II

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20