Product data sheet


LUCAS XI (1-ARMED BEADED) 9.849.2152.16 LEIPZIGER LEUCHTEN






Mounting height 6.00 m. Other heights please inquire. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - Scope of supply includes reinforced and hot-galvanized triple offset Pole dia. 76 mm inclusive painted bracket made of spezial steel Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



Nominal lamp power	50 W	LOR	83%
Lamp flux	3500 lm	ULOR	2%
Luminous efficacy	47 lm/W	Total flux	2901 lm
CCT	2000 K	Total power	62 W
CRI	25		



1 x High	pressure	sodium	vapour	lamp

5 1			
Nominal lamp power	70 W	LOR	83%
Lamp flux	5600 lm	ULOR	2%
Luminous efficacy	56 lm/W	Total flux	4642 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode	Electric
Pole top mounted	System
Shape and measurements	Protecti
Height: 19.69 in	IP: 55

Diameter: 22.44 in

n power: 62-83 W

tion