
Product data sheet


LINEDO_4,5M_OH_11111111
9545OH.843.476.003
RZB



IP 54 IK 04


LINEDO, 212 W, 29200 lm, 840, black, DALI Continuous line luminaire, L 4547 B 58 H 91

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	26.5 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	26.5 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	26.5 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	26.5 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	26.5 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	26.5 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	26.5 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26.5 W	CRI	80
Total flux	3650 lm	LOR	100%
Luminous efficacy	138 lm/W	Total power	26.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 179.02 in
Height: 3.58 in

Adjustability

Fixed

Electric

System power: 212 W

Protection

IP: 54
IK: 04