


# Product data sheet

LENNART II (2-ARMIG)  
9.108.5367.03  
LEIPZIGER LEUCHTEN



Lennart - One or double bracket pole luminaire in a clean contemporary look to illuminate roads, streets, squares or residential areas -Luminaire glazing made of UV-stabilised impact resistant opal polycarbonate -Computer-optimised reflector system for DULUX lamps ensures excellent illumination -Column with door at the base for junction box, bracket and luminaire body made of stainless steel and available either powder coated in any RAL- or DB-colour as required or brushed and passivated -Including special square column, bracket(s) and gear tray -Housing folds out for lamp change -Simple wiring via a mains connection within the base of the luminaire -Three mounting configurations: root (1), flange plate (2) or flange plate in order to pave over (3)


## Light output 1



### 2 x Compact fluorescent lamp

Nominal lamp power	36 W	LOR	33%
Lamp flux	2900 lm	Total flux	1887 lm
Luminous efficacy	24 lm/W	Total power	78 W
CCT	2899 K		
CRI	90		

## Light output 2



### 2 x Compact fluorescent lamp

Nominal lamp power	36 W	LOR	33%
Lamp flux	2900 lm	Total flux	1887 lm
Luminous efficacy	24 lm/W	Total power	78 W
CCT	2899 K		
CRI	90		

## Mounting mode

Pole integrated, Pole top mounted

## Shape and measurements

Length: 23.62 in  
Width: 11.81 in  
Height: 3.94 in

## Electric

System power: 156 W  
Appliance Class: I

## Protection

IP: 55  
IK: 08

## Adjustability

Height adjustable