


# Product data sheet

UNILED ISOSAFE WHITE 670LM 2700K RA 98 TRAILING EDGE DIMMING  
7021989042013  
SG ARMATUREN



Attractive downlight for indoor and outdoor use. Mounted directly in the insulation. Well integrated LED chip, dimmable via phase-dimming or DALI driver (not IsoSafe). Made of die-cast powder-coated aluminium with a 10-year corrosion warranty or brushed steel (only indoors), glass diffuser. 42-degree scattering angle via reflector. 35 mm in total height, Flexible hole dimensions Ø76–Ø83. Tool-free mounting in mounting box for direct 230 V with loopable quick clips and automatic strain relief. IP54, Class II Light distribution Direct Light technic LED (not exchangeable) 8.5W 2700K Ra 98 SDCM 2 L90/B10 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II SELV IP54 Materials and finish Housing: Aluminium Colour: Matt white (RAL 9003) Optics: Tempered glass Mounting/Connection Recessed, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 77, B16: 123, C10: 77, C16: 123

## Light output 1



1 x LED			
Nominal lamp power	8.5 W	LOR	100%
Lamp flux	670 lm	Total flux	670 lm
Luminous efficacy	79 lm/W	Total power	8.5 W
CCT	2700 K		
CRI	98		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 3.70 in  
Width: 3.70 in  
Height: 1.49 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 8.5 W  
Appliance Class: II

## Protection

IP: 54