

Product data sheet

AMBIANE AP RGBWW 80°
240
ANOLIS




IP
54

IK
08



Compact and powerful downlight from Ambiane range is suitable for ambient lighting applications, wall washing and accent lighting where light quality is of the utmost importance. Its high CRI output, simple control mode with CCT, green correction, and perfectly matching dimming curve with tungsten lamps give lighting designers a unique solution without any compromises. Available in RGBW and tunable white CCT versions, along with two beam angles options, the cool-running Ambiane AP is UV or IR radiation free making it ideal for a wide array of applications including theatres, auditoriums, allrooms, hotels, offices, restaurants, retail environments and more. With both DMX and DALI control options, combined with a highly efficient LED source and high quality reflectors for optimum light output, the Ambiane AP can produce truly dramatic results!

Light output 1



1 x LED			
Nominal lamp power	47 W	LOR	100%
Lamp flux	1672 lm	Total flux	1672 lm
Luminous efficacy	36 lm/W	Total power	47 W
CCT	2700 K		
CRI	83		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.53 in
Diameter: 9.13 in

Adjustability

Fixed

Electric

System power: 47 W
Appliance Class: III

Protection

IP: 54
IK: 08