



# Product data sheet

MAX MINI SQUARE  
BA11-P2W8M3BBI8  
LEDSC4




LedsC4 Max Mini Square BA11-P2W8M3BBI8 Recessed uplighting for outdoor use. Metres of cable included: 1. Structure material: Stainless steel AISI316, Aluminium. Structure finish: Gun Metal PVD. Diffuser material: Glass. Diffuser finish: Transparent. UV protection. Warranty: 5 Years. Product net weight (Kg): 0.14 Product width or diameter (mm): 47 Product height (mm): 35 Ø of the hole for recessing (mm): 33 Class 3. IP: IP66-IP67. IK: IK04. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Maximum power of light source: 2.2W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 19.7. Photobiological risk: RG2. Real flux (lm): 191. Real lm/W: 87. Voltage: 3. Equipment included: No, but it is needed. Total power: 2.2.


## Light output 1



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 1 x LED            |         |             |        |
| Nominal lamp power | 2.1 W   | LOR         | 100%   |
| Lamp flux          | 191 lm  | Total flux  | 191 lm |
| Luminous efficacy  | 91 lm/W | Total power | 2.1 W  |
| CCT                | 3000 K  |             |        |
| CRI                | 80      |             |        |



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 1 x LED            |         |             |        |
| Nominal lamp power | 2.5 W   | LOR         | 100%   |
| Lamp flux          | 184 lm  | Total flux  | 184 lm |
| Luminous efficacy  | 74 lm/W | Total power | 2.5 W  |
| CCT                | 3000 K  |             |        |
| CRI                | 80      |             |        |



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 1 x LED            |         |             |        |
| Nominal lamp power | 2.1 W   | LOR         | 100%   |
| Lamp flux          | 191 lm  | Total flux  | 191 lm |
| Luminous efficacy  | 91 lm/W | Total power | 2.1 W  |
| CCT                | 3000 K  |             |        |
| CRI                | 80      |             |        |

**Mounting mode**

Floor recessed

**Shape and measurements**

Length: 1.85 in

Width: 1.85 in

Height: 1.38 in

**Adjustability**

Fixed

**Electric**

System power: 2.1-2.5 W

Appliance Class: III

**Protection**

IP: 67

IK: 04