


Product data sheet

LINEDO_4,5M_90_11001100
954590.850.4M0.522
RZB




IP
54


IK
03

LINEDO, 33. 69 W, 6800. 13800 lm, 850, aluminium, on/off Continuous line luminaire, L 4547 B 58 H 76


Light output 1




1 x LED			
Nominal lamp power	8.3 W	LOR	100%
Lamp flux	1700 lm	Total flux	1700 lm
Luminous efficacy	205 lm/W	Total power	8.3 W
CCT	5000 K		
CRI	80		



1 x LED			
Nominal lamp power	10.3 W	LOR	100%
Lamp flux	2050 lm	Total flux	2050 lm
Luminous efficacy	199 lm/W	Total power	10.3 W
CCT	5000 K		
CRI	80		




1 x LED			
Nominal lamp power	17.3 W	LOR	100%
Lamp flux	3450 lm	Total flux	3450 lm
Luminous efficacy	199 lm/W	Total power	17.3 W
CCT	5000 K		
CRI	80		



1 x LED

Nominal lamp power	14.5 W
Lamp flux	2950 lm
Luminous efficacy	203 lm/W
CCT	5000 K
CRI	80

LOR	100%
Total flux	2950 lm
Total power	14.5 W




1 x LED

Nominal lamp power	12.5 W
Lamp flux	2550 lm
Luminous efficacy	204 lm/W
CCT	5000 K
CRI	80

LOR	100%
Total flux	2550 lm
Total power	12.5 W


Light output 2



1 x LED

Nominal lamp power	17.3 W
Lamp flux	3450 lm
Luminous efficacy	199 lm/W
CCT	5000 K
CRI	80


LOR	100%
Total flux	3450 lm
Total power	17.3 W



1 x LED

Nominal lamp power	14.5 W
Lamp flux	2950 lm
Luminous efficacy	203 lm/W
CCT	5000 K
CRI	80


LOR	100%
Total flux	2950 lm
Total power	14.5 W



1 x LED

Nominal lamp power	12.5 W
Lamp flux	2550 lm
Luminous efficacy	204 lm/W
CCT	5000 K
CRI	80


LOR	100%
Total flux	2550 lm
Total power	12.5 W



1 x LED

Nominal lamp power	10.3 W
Lamp flux	2050 lm
Luminous efficacy	199 lm/W
CCT	5000 K
CRI	80

LOR	100%
Total flux	2050 lm
Total power	10.3 W




1 x LED

Nominal lamp power	8.3 W
Lamp flux	1700 lm
Luminous efficacy	205 lm/W
CCT	5000 K
CRI	80

LOR	100%
Total flux	1700 lm
Total power	8.3 W


Light output 3



1 x LED

Nominal lamp power	17.3 W
Lamp flux	3450 lm
Luminous efficacy	199 lm/W
CCT	5000 K
CRI	80


LOR	100%
Total flux	3450 lm
Total power	17.3 W



1 x LED

Nominal lamp power	14.5 W
Lamp flux	2950 lm
Luminous efficacy	203 lm/W
CCT	5000 K
CRI	80


LOR	100%
Total flux	2950 lm
Total power	14.5 W



1 x LED

Nominal lamp power	12.5 W
Lamp flux	2550 lm
Luminous efficacy	204 lm/W
CCT	5000 K
CRI	80


LOR	100%
Total flux	2550 lm
Total power	12.5 W



1 x LED

Nominal lamp power	10.3 W
Lamp flux	2050 lm
Luminous efficacy	199 lm/W
CCT	5000 K
CRI	80

LOR	100%
Total flux	2050 lm
Total power	10.3 W




1 x LED

Nominal lamp power	8.3 W
Lamp flux	1700 lm
Luminous efficacy	205 lm/W
CCT	5000 K
CRI	80

LOR	100%
Total flux	1700 lm
Total power	8.3 W


Light output 4



1 x LED

Nominal lamp power	8.3 W
Lamp flux	1700 lm
Luminous efficacy	205 lm/W
CCT	5000 K
CRI	80


LOR	100%
Total flux	1700 lm
Total power	8.3 W



1 x LED

Nominal lamp power	14.5 W
Lamp flux	2950 lm
Luminous efficacy	203 lm/W
CCT	5000 K
CRI	80


LOR	100%
Total flux	2950 lm
Total power	14.5 W



1 x LED


Nominal lamp power	17.3 W
Lamp flux	3450 lm
Luminous efficacy	199 lm/W
CCT	5000 K
CRI	80

LOR	100%
Total flux	3450 lm
Total power	17.3 W



1 x LED

Nominal lamp power	12.5 W	LOR	100%
Lamp flux	2550 lm	Total flux	2550 lm
Luminous efficacy	204 lm/W	Total power	12.5 W
CCT	5000 K		
CRI	80		



1 x LED

Nominal lamp power	10.3 W	LOR	100%
Lamp flux	2050 lm	Total flux	2050 lm
Luminous efficacy	199 lm/W	Total power	10.3 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in

Width: 179.02 in

Height: 2.99 in

Adjustability

Fixed

Electric

System power: 33.2-69.2 W

Protection

IP: 54

IK: 03