Product data sheet

DIONE LED PLUS ASYMMETRIC DP 2150LM 830 IP65 ANTYWANDAL (21W)
943195
LENA LIGHTING



943195 DIONE LED PLUS ASYMMETRIC DP 2150lm 830 IP65 ANTYWANDAL (21W) Designed from scratch surface mounted, round LED luminaire with integrated, energy saving LED panel and asymmetrical light distribution. The fitting introduces new solutions to improve the light distribution and balance of the temperatures. It is characterized by high lighting efficiency and very high IP65 ingress protection. Specially profiled diffuser made of vandal-resistant PC allows to keep the highest degree of impact resistance IK10. It uses a number of proven solutions affecting the speed and ease of the assembly (suspension kit for the diffuser, readiness for through wiring) and component security: diffuser integrated with LED panel. Also available is a body made of ASA material, with excellent UV resistance, suitable for outdoor use. The ceiling ring is used to cover the gap between the luminaire and the surface on which it is mounted. The accessory can be used in prison cells.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22 W	CRI	80
Total flux	2150 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	22 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.53 in
Diameter: 13.39 in

Adjustability

Fixed

Design

Material impression: Matt, Plastic
Color of housing: White

Electric

System power: 22 W
Ballast: ECG
Appliance Class: I

Protection

IP: 65
IK: 10
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -4...95°F