
Product data sheet

FLOODLIGHTS - AZTEC FLOODLIGHT ASYMETRIC 3000K
AAZT5/ASY/1 (240W 3000K)
ANSELL LIGHTING



• High performance die-cast aluminium LED floodlight • High output, high efficiency asymmetric lens technology for anti-light pollution • Integral photocell with 2 x lux settings and (deleted 'on-') off options • 10KV surge protection on 120W to 320W, 6KV surge protection on 20W to 80W • Marine grade construction ideal for coastal and adverse weather, swimming pool and chemical plant applications • CCT selectable between 3000K, 4000K and 5000K • Fast fit lever terminals ensure easy and speedy loop-in, loop installation • Pre-installed breathable gland prevents internal moisture accumulation • LED lifespan L80 100,000 hours • Operating Temp -30°C - 50°C • Non-dimmable

Light output 1



1 x LED

Nominal lamp power	240 W	LOR	100%
Lamp flux	38846 lm	Total flux	38844 lm
Luminous efficacy	162 lm/W	Total power	240 W
CCT	3000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 17.05 in
Width: 15.28 in
Height: 3.27 in

Adjustability

Rotatable, Tiltable

Design

Designer: Dominic Harkness

Electric

System power: 240 W

Protection

Designation labels: CE