Product data sheet


PASO2 Q190 4/2,5W LED832 230V SSP
60813732
ZUMTOBEL



IP 67 IK 10

Buried uplighter, surround, square (overlapping); accent spotlight with superspot beam pattern, approx. 6°; lamp(s): 4/2.5W (PowerLEDs with lens optic), ±15° tilt, light colour: warm white (3200K); power consumption 10W; includes control gear; mains voltage 220-240V 50/60Hz; power connection: 3-pole terminal strip; recessed housing: diecast aluminium, white powder-coated finish; PG cable gland; through-wiring possible; partially frosted glass cover; max. surface temperature of glass panel 35°C; stainless steel trim with Camlock catches (no screws visible); maximum load: 1,000kg pedestrian traffic; IP67 degree of protection, class of protection I; includes gasket to protect against water penetrating between luminaire unit and concrete casting surround; concrete casting surround kit must be used for installation in concrete floors or plaster (please order separately); floor cut-out for concrete casting surround, circular: Ø190mm, square:190mmx190mm; floor cut-out for installation in wooden and cavity floors, circular: Ø182mm, square:182mmx182mm, recessed depth: 207 mm; weight: 4.25 kg; Please note: always use flexible leads e.g. H07RN-F when installing the luminaire; if fitted in elevated wooden floors or as downlight in ceiling panels, luminaire requires overlapping trim and installation kit for wooden and cavity floors (please order separately).

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	99
Total flux	492 lm	LOR	100%
Luminous efficacy	49 lm/W	ULOR	100%
		Total power	10 W

Mounting mode

Floor recessed

Shape and measurements

Length: 8.23 in
Width: 8.23 in
Height: 8.35 in
Weight: 4.3 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 10 W
Voltage: 230-240 V AC
Appliance Class: I

Protection

IP: 67
IK: 10
Designation labels: CE