


Product data sheet

INDIVIDUAL BATTEN LUMINAIRE ICE BASIS M600 12W 1380LM CRI > 1002.5977 - ICE BAS SM M600 LED1380-830 DALI
REGENT



Individual batten luminaire ICE Basis m600, with LED, system power: 12 W, standby power 0.5 W, luminous flux of luminaire 1380 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L70 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, housing in steel sheet, white, diffuser in polycarbonate (PC) satin blend white, all-round beam, 1 integral control gear, DALI2, protection class I, ingress protection IP20, glow wire test 850 °C, impact strength: IK 07, this product contains a light source of energy efficiency class B and EPREL registration number: 1133161 L = 577 mm, B = 65 mm, H = 58 mm

Light output 1



1 x LED			
Nominal lamp power	12 W	LOR	100%
Lamp flux	1380 lm	ULOR	4%
Luminous efficacy	115 lm/W	Total flux	1380 lm
CCT	3000 K	Total power	12 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 22.72 in

Width: 2.56 in

Height: 2.28 in

Adjustability

Fixed

Electric

System power: 12 W

Appliance Class: I

Protection

IP: 20

IK: 07