Product data sheet

OUTDOOR LIGHTING
V1-S1-00496-40L30-6603027 TORNADO URBAN 30W 2700K
VARTON



IP 66 IK 09

LED street light luminaire. Tool-free access to the driver. Adjustable spigot. Cast aluminum housing, tempered protective glass. Application: roads and streets. Installation: pole and side-entry mounted (Ø48mm-60mm). Ingress protection (IP): IP66 Impact resistance: IK09 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Mounting method: Side-entry Suitable for top end size, mm: 48...60 Power factor: 0,95 Color rendering index: 70-79 Nominal voltage, V: 220...230 https://www.varton.ru/products/ulichnoe-osveshchenie/tornado/tornado-urban-dlya-goroda/svetodiodnyy-svetilnik-varton-ulichnyy-tornado-30-vt-kreplenie-na-konsol-2700-k-ral9003-belyy-muar/

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3600 lm	Total flux	3600 lm
Luminous efficacy	120 lm/W	Total power	30 W
CCT	2700 K		
CRI	70		

Mounting mode

Pole integrated

Shape and measurements

Length: 22.36 in
Width: 9.06 in
Height: 4.06 in

Adjustability

Fixed

Electric

System power: 30 W

Protection

IP: 66
IK: 09