


Product data sheet

VANCOUVER 29 SURFACE FACADE LUMINAIRES
VA-30032-40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW30, RGBW40 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	10.8 W	CRI	80
Total flux	119 lm	LOR	100%
Luminous efficacy	11 lm/W	Total power	10.8 W

Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	12.8 W	CRI	-50
Total flux	20 lm	LOR	100%
Luminous efficacy	2 lm/W	Total power	12.8 W

Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	12.6 W	CRI	-18
Total flux	125 lm	LOR	100%
Luminous efficacy	10 lm/W	Total power	12.6 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	8.9 W	CRI	-29
Total flux	84 lm	LOR	100%
Luminous efficacy	9 lm/W	Total power	8.9 W

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Height: 23.62 in
Diameter: 9.45 in
Weight: 15.8 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 45.1 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C