Product data sheet


ROTAO100 127-5D1I-10GGE/840, S
127-5D1I-10GGE/840
HALLA



IP 20


127-5D1I-10GGE/840, S Luminaire suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 2000 x 2000 x 87 mm Type of installation: Suspended Distribution: Direct-indirect Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 7 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 8 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 9 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Light output 10 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	15.11 W	CRI	80
Total flux	1377 lm	LOR	90%
Luminous efficacy	91 lm/W	Total power	15.11 W

Mounting mode

Pendant

Shape and measurements

Height: 3.43 in

Diameter: 78.74 in

Adjustability

Fixed

Electric

System power: 151.1 W

Appliance Class: I

Protection

IP: 20