Product data sheet


P.THIRTY SURFACE X-SEG.HOR. BLACK OBD
P30-AXFH9005C1840V3B
PLANLICHT



IP 20 CE


LED VO 4000K 16,7W 2740lm DALI CRI90 https://katalog.planlicht.com/en-gb/search?q=p.thirty&type=1-profile-segment

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.09 W	CRI	90
Total flux	343 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	2.09 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.09 W	CRI	90
Total flux	343 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	2.09 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.09 W	CRI	90
Total flux	343 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	2.09 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.09 W	CRI	90
Total flux	343 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	2.09 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.09 W	CRI	90
Total flux	343 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	2.09 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.09 W	CRI	90
Total flux	343 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	2.09 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.09 W	CRI	90
Total flux	343 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	2.09 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.09 W	CRI	90
Total flux	343 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	2.09 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 8.46 in
Width: 28.43 in
Height: 1.38 in

Adjustability

Fixed

Electric

System power: 16.7 W

Protection

IP: 20
Designation labels: CE