

Product data sheet


LXEP8-50VL-DFA-EDU
CURRENT



IP
48

The LXEP vaportite fixture is for indoor parking garage applications. Comes standard with IP65, IP66, IP67 rating. Replaces fluorescent or HID for quick ROI. Parking Garage luminaire incorporating LED technology, Long life 60,000 hour LEDs at L80 for reduced maintenance, Available in 2', 4', or 8' lengths, IP65/66 all sizes, IP67 4' and 8', Fiberglass housing with F1 weatherability rating, standard, Smooth housing for easy cleaning, Gasket is non-porous to ensure seal, Impact modified acrylic lens equivalent to 100% DR, Lens selections are deep profile frost (DFA) standard, or clear (DCA) optional, Lens firmly secured with captive tamper resistance ready polyacetal (POM) latches, Stainless steel latching optional, Removable gear tray electrical access for modular replaceability, Emergency battery pack installed, optional on most models, Standard ambient -20°C to 50°C (See table for maximum rating), Includes stainless steel surface mounting brackets, Occupancy and/or daylight sensing accessories available, ControlScope® compatible, UL Sanitation certified to NSF standards, DLC® (DesignLights Consortium) Qualified - see www.designlights.org, Five year warranty,

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	123 W	CRI	80
Total flux	15721 lm	LOR	100%
Luminous efficacy	128 lm/W	ULOR	11%
		Total power	123 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 5.98 in
Width: 98.03 in
Height: 3.23 in

Adjustability

Fixed

Design

Material impression: Glass
Color of housing: White

Electric

System power: 123 W

Protection

IP: 48