


Product data sheet

TYP L96 PC 5S
TYPHON
DEXTRA



Typhon - 1500mm Single, IP65 Surface mounted moisture resistant luminaire. GRP body, polycarbonate diffuser. Complete with tooled access Stainless steel diffuser retaining clips. Options: LE3 - Lithium Emergency (421 lumen output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) R44 - Reacta 44 Daylight and Presence Detection Sensor R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode* RLS - Reacta-Link Wireless Presence RLM - Reacta-Link Wireless Microwave Presence & Bright Out RCME - Reacta-Control Wireless Microwave On/Off RCMC - Reacta-Control Wireless Microwave Corridor Mode* *Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off.

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 53 W | CRI | 80 |
| Total flux | 8256 lm | LOR | 100% |
| Luminous efficacy | 156 lm/W | ULOR | 4% |
| | | Total power | 53 W |

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 61.69 in
Width: 4.25 in
Height: 4.13 in

Adjustability

Fixed

Electric

System power: 53 W
Ballast: ECG
Controller: DALI

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor, Presence sensor

Protection

IP: 65
Designation labels: CE