


Product data sheet

SPL14 - SPY 27 93030 MDL
27313 9320
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named SPL14 - SPY 27 93030 MDL, available in the colour(s): black, flemish bronze, flemish gold, gold coloured, white. This luminaire can be used with the following 48V lighting system(s): D-LINER 19 SL PROFILE SET, SPLITLINE 14 - PROFILE. This luminaire is equipped with LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: MDL = 1-10V or DALI or push button. Light distributor: reflector 30°.

Light output 1



1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	787 lm	Total flux	573 lm
Luminous efficacy	131 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	6 W	LOR	73%
Lamp flux	787 lm	Total flux	573 lm
Luminous efficacy	131 lm/W	Total power	6 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed, Contact rail, Wall recessed

Shape and measurements

Length: 0.28 in
Width: 6.30 in
Height: 0.04 in

Electric

System power: 6 W
Appliance Class: II

Protection

IP: 20
Designation labels: CE