Product data sheet


INFINITE PRO 1136MM SURFACE HEXA-CELL
AK14-34W9HCD314
LEDSC4



IP 40


LedsC4 Infinite Pro 1136mm Surface Hexa-Cell AK14-34W9HCD314V2 Lineal lighting system for indoor use. For downlighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Hexa-Cell. Warranty: 5 Years. Product net weight (Kg): 3.18 Product length (mm): 1136 Product width or diameter (mm): 52 Product height (mm): 90 Class 1. IP: IP40. LED. No. of lampholders or LEDs: 1. Driver brand: TCI. Maximum power of light source: 31.1W. Colour temperature: 3000K. Colour rendering index: 92. MacAdam Steps: 3. Hours of life: 80.000h L80B20. UGR: 10.1. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 1208. Real lm/W: 37. Voltage / frequency range: 220-240/50-60Hz. Voltage: 96. Equipment included: Yes. Total power: 32.6. Power factor: 0.95. Dimmable equipment included: DALI-2/PUSH.

Light output 1 (emergency)



1 x LED

Nominal lamp power	32.6 W	LOR	100%
Lamp flux	1208 lm	Total flux	1208 lm
Luminous efficacy	37 lm/W	Total power	32.6 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	3.8 W	LOR	100%
Lamp flux	65 lm	Total flux	65 lm
Luminous efficacy	17 lm/W	Total power	3.8 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 44.72 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 3.8-32.6 W
Appliance Class: I

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 40