
Product data sheet

LINEAR LIGHTING

V1-R0-90823-02OPA-4002030 X-LINE 1,00 M STAND-ALONE 20W 3000K EM 1H


VARTON



IP 40 IK 01

• Extruded aluminum luminaire • Standalone Application • Retail spaces • Administrative facilities Installation • Surface-mounted • Suspended Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Pendant Ingress protection (IP): IP40 Radiation angle: Radiation angle, °: 100 Impact resistance: IK01 Power factor: 0,9 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/x-line-odinochnye/x-line-1-00-m-odinochnye/cvetilnik-varton-x-line-1-m-20-vt-odinochnyy-podvesnoy-3000-k-1003x63x100-mm-ip40-ral9005-chernyy-mu_2/

Light output 1



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	1900 lm	Total flux	1900 lm
Luminous efficacy	95 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 39.49 in

Width: 2.48 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 20 W

Protection

IP: 40

IK: 01