Product data sheet

QAW423WL-SI-BM - RUND
QAW423WL-SI-BM
RP-TECHNIK



IP 20 IK 03 CE

Round metal luminaire for general lighting and the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838. In mains operation the luminaire works with 26W / 2.300lm LED. The general light is switched independently of the emergency light via the motion detector, which is not visible from the outside.

Light output 1



1 x LED

Nominal lamp power	264 W	LOR	89%
Lamp flux	2300 lm	Total flux	2051 lm
Luminous efficacy	9 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

Light output 2 (emergency)



1 x LED

Nominal lamp power	26.4 W	LOR	89%
Lamp flux	250 lm	Total flux	223 lm
Luminous efficacy	9 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Wall recessed

Shape and measurements

Height: 4.45 in
Diameter: 15.55 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 60 W
Appliance Class: 0

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20
IK: 03
Designation labels: CE

Other operating numbers

Ambient temperature range: 23...95°F