Product data sheet


SQING PENDANT DI/ID SILVER
R54H07Q-9006E2830L1S
PLANLICHT



IP 40


LED LO 3000K 52W 3856lm https://katalog.planlicht.com/en-us/fam-sqing/

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	482 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	50%
		Total power	6.5 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	482 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	50%
		Total power	6.5 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	482 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	50%
		Total power	6.5 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	482 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	50%
		Total power	6.5 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	482 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	50%
		Total power	6.5 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	482 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	50%
		Total power	6.5 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	482 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	50%
		Total power	6.5 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	80
Total flux	482 lm	LOR	100%
Luminous efficacy	74 lm/W	ULOR	50%
		Total power	6.5 W

Mounting mode

Pendant

Shape and measurements

Length: 29.80 in
Width: 29.80 in
Height: 2.36 in

Adjustability

Fixed

Electric

System power: 52 W

Protection

IP: 40