

Product data sheet

ECHO L 265 WHITE 5700K 600MA


7476829

HIDE-A-LITE



Flexible luminaire with reflector technology and a high-positioned light source for very good anti-glare properties. Instead of replacing with cover rings, choose a complete luminaire in the size you need. Echo is a large product family for holes from 103-300mm. Dimmable all-round luminaire for public environments that need a lot of light, such as in rooms with high ceilings, corridors or shops. Perfect for new installations and to replace compact fluorescent tube luminaires. Selectable colour temperature via DIP-switch. Echo M and Echo L have adjustable lumen output via DIP-switch Power. Comes complete with driver for phase dimming or DALI-2. DALI-2 comes with Q-box Micro, push-in terminals and screwless strain relief. Dimmable with most common dimmers on the market.

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 5700 K |
| Nominal lamp power | 22.4 W | CRI | 80 |
| Total flux | 2353 lm | LOR | 100% |
| Luminous efficacy | 105 lm/W | Total power | 22.4 W |

Mounting mode

Ceiling recessed, Contact rail

Shape and measurements

Height: 4.33 in

Diameter: 10.43 in

Adjustability

Fixed

Electric

System power: 22.4 W

Ballast: ECG

Appliance Class: II

Protection

IP: 44

Designation labels: CE