Product data sheet

ECHO L 265 WHITE 5700K 600MA 7476829

HIDE-A-LITE










Flexible luminaire with reflector technology and a high-positioned light source for very good anti-glare properties. Instead of replacing with cover rings, choose a complete luminaire in the size you need. Echo is a large product family for holes from 103-300mm. Dimmable all-round luminaire for public environments that need a lot of light, such as in rooms with high ceilings, corridors or shops. Perfect for new installations and to replace compact fluorescent tube luminaires. Selectable colour temperature via DIP-switch. Echo M and Echo L have adjustable lumen output via DIP-switch Power. Comes complete with driver for phase dimming or DALI-2. DALI-2 comes with Q-box Micro, push-in terminals and screwless strain relief. Dimmable with most common dimmers on the market.

Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	CCT	5700 K
22.4 W	CRI	80
2353 lm	LOR	100%
105 lm/W	Total power	22.4 W

Mounting mode

Ceiling recessed, Contact rail

Shape and measurements

Height: 4.33 in Diameter: 10.43 in

Adjustability

Fixed

Electric

System power: 22.4 W

Ballast: ECG

Appliance Class: II

Protection

IP: 44

Designation labels: CE