



Product data sheet

INFINITE HIGH OUTPUT 494MM
90-A063-60-00
LEDSC4



LedsC4 Infinite High Output 494mm 90-A063-60-00 Low voltage for indoor use. For downlighting. Structure material: Aluminium. Structure finish: Black. Diffuser material: PVC. Diffuser finish: White. Warranty: 5 Years. Product net weight (Kg): 0.18 Product length (mm): 462 Product width or diameter (mm): 20 Product height (mm): 35 Class 3. IP: IP20. LED. No. of lampholders or LEDs: 1. LED brand: BRIDGELUX. Maximum power of light source: 12.6W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 24.8. Photobiological risk: RG1. % de Flickering: +/- 5%. Real flux (lm): 1361. Real lm/W: 108. Voltage / frequency range: 48. Voltage: 3. Equipment included: No, but it is needed. Total power: 12.6. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED			
Nominal lamp power	12.6 W	LOR	100%
Lamp flux	1024 lm	Total flux	1024 lm
Luminous efficacy	81 lm/W	Total power	12.6 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling mounted, Wall recessed

Shape and measurements

Length: 0.91 in
Width: 19.45 in
Height: 0.71 in

Adjustability

Fixed

Electric

System power: 12.6 W
Appliance Class: III

Protection

IP: 20