Product data sheet

LED PFM FLOODLIGHT HP 500W 840 55D MV

4058075418677


LEDVANCE



LEDVANCE®LED PERFORMANCE HIGH POWER FLOOD LIGHT combine a high efficacy, precision optics and reliability into a cost-effective solution. It perfectly replaces the traditional 1KW to 2KW HID luminaire into a more stylish, rugged, flexible and high-performance professional luminaires. Robust die cast aluminum housing rated IP 65 and IK 08 provides reliable ingress protection and long-term reliability. High guality heat dissipation and UV resistant integral PC lens deliver uniform and accurate illumination. It is available in 4 beam angles for flexible use in different high-power application of indoor and outdoor. Aesthetic and optimized design. Standard 6500K&4000K CCT, Ra>80. System efficacy up to 120lm/W. High quality integral PC lens. Adjustable mounting bracket design offers flexibility and convenience in use. Compact housing with high efficiency and reliable power supply. IP65 / IK08. 10KV surge protection. 50,000hrs long lifetime reduces maintenance cost.

IK 08

Light output 1 (integrated)



Lamp type Nominal lamp power Total flux Luminous efficacy

LED 500 W 60000 lm 120 lm/W

Total power

CCT

CRI

LOR

4000 K 100% 500 W

80

Mounting mode

Wall mounted

Shape and measurements

Length: 0.04 in Width: 0.04 in Height: 0.39 in

Adjustability

Free

Electric

System power: 500 W

Protection

IP: 65 IK: 08