



# Product data sheet

ATX FELED LINEAR 5K LUMEN NEMA TYPE V 5000 K CCT  
 FELED5CBUSADE  
 APPLETON (EMERSON EGS)




ATX FELED Series Nonmetallic LED Explosionproof Luminaires Ceiling/ Pendant Mount Emergency Luminaire 180 Min backup 5000 K CCT/ 70 CRI Pendant/Ceiling Mount BU:-120-277 Vac, 50/60Hz, 170-300 Vdc, BD:-100-240 Vac 50/60 Hz 3/4" NPT Hub Clear polycarbonate cover Zone 1 and 2 Zone 21 & 22 Ex. II 2 GD IP 66 IK 10 Refer to catalog for additional options

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	5181 K
Nominal lamp power	1 W	CRI	86
Total flux	800 lm	LOR	100%
Luminous efficacy	800 lm/W	ULOR	6%
		Total power	1 W

## Light output 2 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	6.65 W	CRI	70
Total flux	800 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	6.65 W

### Mounting mode

Pendant

### Shape and measurements

Length: 1.77 in

Width: 41.34 in

Height: 4.80 in

### Adjustability

Tiltable, Height adjustable

### Electric

System power: 7.65 W

Appliance Class: II

### Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

### Protection

IP: 67

IK: 10

Explosion zone suitability: 1, 21