Product data sheet

VEKTOR XXL 3K
E7220787
CARDI



IP 44 IK 06

Vektor är en allmänljusarmatur IP44, utformad för att ge lägre miljöpåverkan både genom sin konstruktion och sitt emballage. Armaturen är till över 98 % återvinningsbar. Vektor har ställbart ljusflöde i fyra lägen. Stomme av återvunnen vitlackerad aluminium (85%) för bra kylning av LED och elektronik, gavlar av vit biobaserad plast, kupa av återvunnen frostad linjeprismatisk akryl ≥ 20%. Monteras dikt tak, lina, på vägg eller konsol. Möjlighet till dos-montage, enligt borranvisning. Armaturen är D-märkt. Kabelinföring Ø 20 mm i vardera gavel samt 2 st Ø 20 mm kabelinföring på ovansidan. Insticksplint i mitten av armaturen 5x2x2,5mm². Vektor har ställbart ljusflöde via dip-switchar direkt på drivdonet, se lumentabell under bilden eller längre ned på produktsidan alt. montageanvisning.

Light output 1



1 x LED

Nominal lamp power	61 W	LOR	100%
Lamp flux	10860 lm	ULOR	7%
Luminous efficacy	178 lm/W	Total flux	10860 lm
CCT	3000 K	Total power	61 W
CRI	80		



1 x LED

Nominal lamp power	46 W	LOR	100%
Lamp flux	7980 lm	ULOR	7%
Luminous efficacy	173 lm/W	Total flux	7980 lm
CCT	3000 K	Total power	46 W
CRI	80		



1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	6280 lm	ULOR	7%
Luminous efficacy	185 lm/W	Total flux	6280 lm
CCT	3000 K	Total power	34 W
CRI	80		



1 x LED

Nominal lamp power	55 W	LOR	100%
Lamp flux	9430 lm	ULOR	7%
Luminous efficacy	171 lm/W	Total flux	9430 lm
CCT	3000 K	Total power	55 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.95 in
Width: 6.41 in
Height: 1.43 in

Adjustability

Fixed

Electric

System power: 34-61 W
Appliance Class: I

Protection

IP: 44
IK: 06