



Product data sheet

LIGHTING FOR RESIDENTIAL COMMON AREAS
V1-U0-T0821-21FD2-6502540 NERO FLEX IP65 25 W 23W 4000K DALI
VARTON



• Round luminaire with homogenous illumination • Changeable decorative plastic frames • Material: plastic housing and frame, PMMA diffuser
Application • Entrances • Lobbies • Corridors • Stairways Installation • Surface-mounted on the wall or ceiling Input voltage (AC, 50Hz), V:
198...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: YXЛ2 Protection class: II Housing material:
Plastic Mounting method: Surface mounting Ingress protection (IP): IP65 Impact resistance: IK08 Power factor: 0,95
<https://www.varton.ru/products/svetilniki-dlya-zhkkh/nero-flex-rus-ip65/zhkkh-nero-flex-rus-23-vt/svetodiodnyy-svetilnik-var-ton-nero-flex-23-vt-4000-k-298kh77-mm-ip65-chernyy-s-ramkoy-polovinka-dali/>

Light output 1



1 x LED			
Nominal lamp power	23 W	LOR	100%
Lamp flux	1750 lm	Total flux	1750 lm
Luminous efficacy	76 lm/W	Total power	23 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.03 in
Diameter: 11.73 in

Adjustability

Fixed

Electric

System power: 23 W

Protection

IP: 65
IK: 08