# Product data sheet


MULTILUME FLOW 4000K VTB CLO
23851-528
FAGERHULT



IP 44

Installation Recessed mounting in ventilated or unventilated suspended ceilings. Two optional designs. VTB – for suspended ceilings with visible T-bars 25 mm. HB – for suspended ceiling with concealed T-bars. Supplement with fixing brackets for fixed suspended ceiling, see accessories. The luminaire must not be covered with insulation. For further details please refer to the assembly instructions on our website. Connection Connection in ballast box. The ballast box can be detached and positioned next to the luminaire. Snap-in terminal block 3x1,5 mm² (5x1,5 mm² where dimming is required). Through-wiring possible. Design Luminaire body in white enamelled sheet steel (RAL 9016). Louvre Opal – Opal plate in frosted acrylic (PMMA). Miscellaneous Enclosure class IP 44 under suspended ceilings and IP 20 above suspended ceilings.

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 19 W | CRI | 80 |
| Total flux | 2859 lm | LOR | 100% |
| Luminous efficacy | 150 lm/W | Total power | 19 W |

### Mounting mode

Ceiling recessed

### Shape and measurements

Length: 23.46 in
Width: 23.46 in
Height: 5.11 in

### Adjustability

Fixed

### Design

Color of housing: White

### Electric

System power: 19 W

### Protection

IP: 44