


Product data sheet

QUADRANA
311728.002
RZB



IP
40

IK
05

Series: Quadrana Type of Protection: IP 40 Protection Class: I Voltage: 230 V / 50 Hz Decorative wall and ceiling luminaire made of pressure die-cast aluminium. Opal PMMA diffuser. Tool-free access with two ellbow lever locks. Integral LED module for direct mains voltage connection. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 300, B 300, H 115 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK05 (0,70 Joule) Luminaire flux LED: 300lm System power: 5W Beam Angle: 106° Unified Glare Ratio: 13,0 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 5 W | CRI | 80 |
| Total flux | 300 lm | LOR | 100% |
| Luminous efficacy | 60 lm/W | ULOR | 22% |
| | | Total power | 5 W |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.81 in
Width: 11.81 in
Height: 4.53 in

Adjustability

Fixed

Electric

System power: 5 W

Protection

IP: 40
IK: 05