


Product data sheet

ARLON WHITE 1100LM 2700K RA>80 TRAILING EDGE DIMMING
7021986536065
SG ARMATUREN



Arlon is an efficient and modern luminaire made from die-cast, powder-coated aluminium. The light source is recessed and slightly angled, making it well-suited to lighting walkways, corridors and other similar spaces thanks to its low levels of glare. Can be dimmed using trailing edge dimming or DALI dimmer (DALI upon request). Easy installation with back plate for mounting, two cable inputs and a quick connector. Can also be used to provide uplight. Light distribution Direct Light technic LED 10W 2700K Ra>80 SDCM 3 L80/B20 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP65 IK10 Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: Polycarbonat (PC) Mounting/Connection Wall, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 31, B16: 50, C10: 52, C16: 85

Light output 1



1 x LED			
Nominal lamp power	10 W	LOR	100%
Lamp flux	1100 lm	Total flux	1100 lm
Luminous efficacy	110 lm/W	Total power	10 W
CCT	2700 K		
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 10.63 in
Width: 1.85 in
Height: 5.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W
Appliance Class: II

Protection

IP: 65
IK: 10