Product data sheet


CEDER-A3-L2WG6-CD15-4000K-2500LM-16.8W
LIGHTRONICS



IK 10

CEDER MAXIMUM CIRCULARITY The conical CEDER luminaire can be used for a wide range of applications in public spaces. The Cedar tree, a hardy survivor, symbolises Lightronics' vision of sustainability and the development goals for the CEDER luminaire. The core values of that vision include corporate social responsibility, social value, circularity, social safety and quality. The CEDER is available in three variants: A1-Bright, A2-White and A3-Night. You can opt for purely functional light, a more diffuse type of illumination or high-comfort illumination. We carry out calculations and simulations to give you a better idea of the lighting experience and make recommendations for optimising lighting comfort and minimising light nuisance.

Light output 1



16 x LED

Nominal lamp power	1.05 W	LOR	87%
Lamp flux	156 lm	Total flux	2165 lm
Luminous efficacy	149 lm/W	Total power	16.8 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Height: 3.94 in
Diameter: 21.34 in

Adjustability

Fixed

Design

Material impression: Aluminum, Matt
Color of housing: Black, Silver gray

Electric

System power: 16.8 W

Protection

IK: 10