

Product data sheet


SRT-SYSTEM IP64-SRGSCXT EP/1500 LED - GERÄTETRÄGER FIX CENTRAL.LINE.OPTIC | DEVICE MOUNT FIX CENTRAL.LI...
13000-8000 840 8258LM IP64 (PHI-EL=856LM) ETM NL-3H VW RAL 9016 (SRT+19542007880)

REGIOLUX



SRT-Quick-fit mounting system, IP 64 device mount, Modullänge/1500. Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Housing colour traffic white RAL 9016; Performance level: Economy Performance (EP) - For cost-sensitive projects, high efficiency and a long service life, Light distribution direct, extra narrow distribution by means of Central.Line.Optic of PMMA plastic, The lens optics have a transparent seal, ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The compact 1-row arrangement of the lenses ensures that the dots merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting; With 3h emergency lighting battery; Luminaire status by visible status LED in luminaire (NL-B3); Luminous flux in emergency light mode 856 lm. Dimensions (LxWxH): 1531mm x 55mm x 37mm Beam angle: 25° (C0) / 55° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 50000h L80/B10 (Tq 25°C) Nominal luminous flux/switching steps: 13200lm/89W, 11800lm/77W, 10300lm/66W, 8300lm/50W Nominal luminous flux-emergency lighting mode: 856lm Luminaire luminous efficiency: 164lm/W-148lm/W Controller: Electronic multi-lumen driver 3h emergency lighting, 4-steps (1 pcs.) System output: 89W-50W Energy efficiency class/light source: C Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (5°C bis 25°C) Ambient temperatur: ta 5°C to 25°C UGR lat./long.: 16.1 / 20.8 (89W) Certification mark: IP64, Protection class I, F, D, HACCP DIN10500/Food/IFS-application-related suitability/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: SRGSCXT EP /1500 LED 13000-8000 840 ETM NL-B3 vw RAL 9016 Article number: 19542007880 Product deep link: <https://www.regiolux.de/en/article/19542007880> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	50.3 W	CRI	80
Total flux	8258 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	50.3 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 50.3 W
Appliance Class: 0

Design

Color of housing: White

Protection

IP: 64

IK: 03

Designation labels: CE