

Product data sheet

LUNIO-STREET - 21W - 2850LM - TYPE IV-L
0877032A-840
ARCLUCE




IP
66

IK
08

IP DEGREE : IP66 IK RATING : IK08 ELECTRICAL INSULATION CLASS: II LUMINAIRE Die-cast aluminium body (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. Wiring on removable galvanized steel tray. Knife-switch for automatic power disconnection when opened. Driver protected against voltage surges. PMMA lenses for LEDs. Screen made of 4mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-3. INSTALLATION Post-top installation (Ø60mm reduction). Supplied with power cable ended (0.15m) by IP66 socket-plug connector with locking ring for cables of diameter 9-12mm.

Light output 1



1 x LED			
Nominal lamp power	21 W	LOR	100%
Lamp flux	2850 lm	Total flux	2850 lm
Luminous efficacy	136 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		

Mounting mode

Pole top mounted

Electric

System power: 21 W

Shape and measurements

Length: 20.47 in
Width: 27.56 in
Height: 4.76 in

Protection

IP: 66
IK: 08

Adjustability

Fixed