



Product data sheet

EASY KAP 105
03.4451.74/HI PAR 51/35W/10°25°40°
FLOS




Luminaire for recessed mounting on ceilings for halogen, metal halide and LED lamps. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).


Light output 1



| | | | |
|------------------------------|---------|-------------|---------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 35 W | Socket | Gx10 |
| Lamp flux | 2100 lm | LOR | 51% |
| Luminous efficacy | 31 lm/W | Total flux | 1080 lm |
| CCT | 3000 K | Total power | 35 W |
| CRI | 84 | | |



| | | | |
|------------------------------|---------|-------------|--------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 35 W | Socket | Gx10 |
| Lamp flux | 2100 lm | LOR | 45% |
| Luminous efficacy | 27 lm/W | Total flux | 950 lm |
| CCT | 3000 K | Total power | 35 W |
| CRI | 84 | | |



| | | | |
|------------------------------|---------|-------------|---------|
| 1 x Metal halide lamp | | | |
| Nominal lamp power | 35 W | Socket | Gx10 |
| Lamp flux | 2100 lm | LOR | 48% |
| Luminous efficacy | 29 lm/W | Total flux | 1014 lm |
| CCT | 3000 K | Total power | 35 W |
| CRI | 84 | | |

Mounting mode

Ceiling recessed

Electric

System power: 35 W

Shape and measurements

Height: 6.38 in

Diameter: 4.13 in

Adjustability

Fixed

Protection

IP: 20