Product data sheet


FREESTANDING LUMINAIRE LIGHTPAD OFFICE FOR TWO PERSON WORKS
2007.8154 - LGTPD4 C2H LED13600-930 WH 2IF1315 SEDI EU
REGENT



IP 20

Freestanding luminaire Lightpad Office for two person workstation, central, with LED, system power: 102 W, standby power 2 x 0.5 W, luminous flux of luminaire 13600 lm, colour rendering index CRI > 90, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, with 2 higher control elements, in aluminium, white, RAL 9016, 2 integral control gears, SensoDim®, with 2 light/movement sensors, 3m power supply cable with IEC 7/7 european plug, base plate, H-shaped, ENEC certified, protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1258590 lower edge of control element 1315 mm, L = 718 mm, B = 636 mm, H = 19 mm, total height = 2000 mm


Light output 1



1 x LED

Nominal lamp power	51 W	LOR	100%
Lamp flux	6800 lm	ULOR	64%
Luminous efficacy	133 lm/W	Total flux	6789 lm
CCT	3000 K	Total power	51 W
CRI	90		

Light output 2



1 x LED

Nominal lamp power	51 W	LOR	100%
Lamp flux	6800 lm	ULOR	64%
Luminous efficacy	133 lm/W	Total flux	6789 lm
CCT	3000 K	Total power	51 W
CRI	90		

Mounting mode

Standing / Bollard

Electric

System power: 102 W

Appliance Class: I

Protection

IP: 20

Shape and measurements

Length: 28.27 in

Width: 24.96 in

Height: 78.90 in

Weight: 26.789 kg

Adjustability

Free

Design

Color of housing: White