Product data sheet


INDUSTRIAL AND WAREHOUSE LIGHTING
V1-IA-7HE71-03G00-6702450 IRON 3.0 0,6 M 24W 5000K TRANSPARENT
VARTON



IP 67 IK 01

Industrial linear luminaire. The next generation of the Iron series (reduced price, optimised range). Aluminum profile, polycarbonate diffuser (transparent/opal). Installation: Suspended 3-6 m height (mounting brackets included in package). Surface-mounted (mounting brackets included in package). The luminaire has a wire for connecting to the mains. Wire length 0.5 meters. Application: Administrative facilities, Industrial facilities, Warehouses, Areas with high moisture and dust environment, and high reliability requirements. Power factor: 0,95 Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Input voltage (DC), V: 190...280 Flicker, %: 5 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP67 Impact resistance: IK01 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/iron-3-0/iron-3-0-0-6-m/svetodiodnyy-svetilnik-varton-ayron-3-0-0-6m-24-vt-5000-k-s-prozrachnym-rasseivatelem/

Light output 1



1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	3100 lm	Total flux	3100 lm
Luminous efficacy	129 lm/W	Total power	24 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.62 in
Width: 4.29 in
Height: 2.60 in

Adjustability

Fixed

Electric

System power: 24 W

Protection

IP: 67
IK: 01