Product data sheet

CODEMASTER LED 600 W NEMA TYPE V
CMLEDW75G5BUG
APPLETON (EMERSON EGS)


EMERSON. APPLETON

IP 67

Codemaster LED Factory Sealed Luminaire Explosionproof , Dust-Ignitionproof 600W equivalent LED 5500 K CCT/ 70 CRI Mounting-Wall BU-120-277V, 50/60Hz 3/4" NPT Hub Clear Glass Globe with Guard Class I, Division 1 & 2, Groups B, C, D Class I, Zone 1, Group IIB + H2 Class II, Division 1, Group E,F, G Class II,Division 2, group F,G. Class III Simultaneous Exposure Type 3R, 4X IP66/67 Suitable for Use in Wet Locations Marine Outside Type (Salt Water) Refer to catalog for additional options

---

Light output 1 (integrated)

Lamp type	LED	CCT	5181 K
Nominal lamp power	132.1 W	CRI	70
Total flux	15037 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	132.1 W

Mounting mode

Wall mounted

Shape and measurements

Height: 7.50 in
Diameter: 7.50 in

Adjustability

Fixed

Electric

System power: 132.1 W

Appliance Class: I

Protection

IP: 67

Explosion zone suitability: 1