Product data sheet


SENSE PRO 600X600 WHITE 4990LM 3000K RA>80 TRAILING EDGE DIMMING
7021982126703 + 7021988204955
SG ARMATUREN



IP 40 IK 10

The Sense panel is well designed and only 10 mm high. A narrow frame ensures attractive look and high efficiency.Sense can be mounted to visible T-rail ceilings without accessories and to concealed T-rail ceilings, DAMPA clip-in ceilings, Troldtekt acoustic panels and Gypsum, and surface-mounted using accessories. This makes Sense an all-round quality panel that can be used everywhere. Sense is available in several lumen packages, phase-dimming or DALI depending on which driver kit is selected (accessory). Light distribution Direct Light technic LED 38W 3000K Ra>80 SDCM 3 L80/B20 >100,000 hrs L90 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class III IP40 IK10 Materials and finish Housing: Aluminium Colour: White smooth (Ral 9016 gloss 30) Optics: Acrylic (PMMA) Mounting/Connection Recessed, Indoor Exposed T-carrier 15/24mm 3 pol Linect / screwless terminal block

Light output 1



1 x LED

Nominal lamp power	38 W	LOR	100%
Lamp flux	4990 lm	Total flux	4990 lm
Luminous efficacy	131 lm/W	Total power	38 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.50 in
Width: 23.50 in
Height: 0.39 in

Adjustability

Fixed

Electric

System power: 38 W
Appliance Class: III

Protection

IP: 40
IK: 10