


Product data sheet

LINEA S LED ECO 588MM 3150LM 840 IP40 MW DALI (20W)
667169
LENA LIGHTING



667169 LINEA S LED ECO 588mm 3150lm 840 IP40 MW DALI (20W) Linea S LED Eco is a surface-mounted and pendant light-line system, representing a new generation of luminaires dedicated to LED technology. The design used allows for easy installation and power connection. The steel body, designed from the ground up, ensures the luminaire's strength and robustness, while the narrow side profile allows installation in hard-to-reach areas. The ECO version is dedicated to investments where the length of individual light lines supplied from a single cable (not including modules with bezels and not including current protection) does not exceed 40m. The light modules are permanently connected to the carrier modules using dedicated cubes. The optics used in the other luminaires of the LINEA S family are possible.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	3150 lm	LOR	100%
Luminous efficacy	158 lm/W	Total power	20 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 23.15 in
Width: 1.97 in
Height: 2.56 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: White

Electric

System power: 20 W
Ballast: ECG
Controller: DALI
Appliance Class: I

Protection

IP: 40
IK: 03

Other operating numbers

Ambient temperature range: -4...95°F