

Product data sheet

SKY L222 OP WH
SKY-LIGHT LED
DEXTRA




IP
20



Sky-Light LED - 1000mm, IP20 High level Luminaire, steel body white powder coated paint finish, injection moulded polycarbonate end caps with customisable colours to suit your corporate identity (subject to minimum quantity) and high transmission angled opal diffusers. Options: E3 - Emergency control gear (699 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) H - High Frequency Dimming (Analogue 1-10v) RLS10 - Reacta-Link Wireless Presence 10M RLS15 - Reacta-Link Wireless Presence 15M RCS - Reacta-Control Wireless, Presence RC18 - Reacta-Control Wireless, Presence & Daylight 4PM - Pre-wired 4 Pole Panel Mount 6PM - Pre-wired 6 Pole Panel Mount SKY 5M SUSP GPLKIT - 5mtr Loop Over Suspension Kit (Two Drops) SKY 10M SUSP GPLKIT - 10mtr Loop Over Suspension Kit (Two Drops) RD - Red End Caps OR - Orange End Caps BL - Blue End Caps PR - Purple End Caps YL - Yellow End Caps GR - Green End Caps GY - Grey End Caps

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|---------|
| Lamp type | | CCT | 4000 K |
| Nominal lamp power | 128.2 W | CRI | 80 |
| Total flux | 18025 lm | LOR | 100% |
| Luminous efficacy | 141 lm/W | ULOR | 4% |
| | | Total power | 128.2 W |

Mounting mode

Pendant

Shape and measurements

Length: 39.49 in
Width: 19.84 in
Height: 3.03 in

Adjustability

Fixed

Electric

System power: 128.2 W
Ballast: ECG

Protection

IP: 20
Designation labels: CE