

Product data sheet


ECLEXPOLFLOOD150IPFC
ECLEXPOLFLOOD150IPFC_RED_HB
PROLIGHTS



IP
65

The EclExpo Flood150 is a compact, bright, and versatile floodlight that is designed to be a substitute for traditional CDM, HMI, and tungsten small floods in tradeshow, theaters, or as a work light. Just like its classic predecessors, but with a custom LED source, this unit features a linear light source combined with a reflector, which ensures a wide coverage of 100° (Horizontal) x 60° (Vertical) of indirect light emission. The EclExpo Flood150 is available in two source variants: - FC, which utilizes RGB+WarmWhite calibrated LED with high Color Rendering. - VW, which uses a bi-color Vari White LED source with a CCT range of 2,700K-6,500K. This unit is incredibly user-friendly, offering immediate stand-alone access through the knobs or through wired DMX/RDM or Wireless CRM (optional). Timeless Elegance meets Green Innovation: The EclExpo Flood150 - Where Classic Beauty Embraces Modern Technology

Light output 1 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	74.45 W	CRI	-40
Total flux	1735 lm	LOR	100%
Luminous efficacy	23 lm/W	Total power	74.45 W

Mounting mode

Ceiling mounted

Electric

System power: 74.45 W

Shape and measurements

Length: 2.60 in

Width: 12.17 in

Height: 7.68 in

Protection

IP: 65

Adjustability

Tiltable