# Product data sheet


PRUNUS-F4-PA07-64LED-4000K-5200LM-30.3W
LIGHTRONICS



IK 10

PRUNUS F DESIGN WITH AN EYE FOR DETAIL The PRUNUS F is a round luminaire and available in four variants. This luminaire has a special appearance and is suitable for a large number of applications, such as residential areas, public squares, parks, business parks, district distributor roads, town and village centres, separate cycle paths and car parks. The PRUNUS F is available with a transparent, flat UV-stabilised polycarbonate light cover (F1/F2), a contoured light cover made from textured polycarbonate (F3) and a flat light cover made from transparent safety glass (F4).

### Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 30.3 W | CRI | 70 |
| Total flux | 74 lm | LOR | 87% |
| Luminous efficacy | 2 lm/W | Total power | 30.3 W |

### Mounting mode

Pole top mounted, Ceiling mounted

### Shape and measurements

Height: 3.94 in
Diameter: 19.69 in

### Adjustability

Fixed

### Design

Material impression: Aluminum
Color of housing: Anthracite / graphite

### Electric

System power: 30.3 W

### Protection

IK: 10