

Product data sheet


NATH S RE 3000K 49 W 700 MA
SIMON LIGHTING



IP
65

SIMON Nath S Óptica RE 3000K 49 W 700 mA. Características técnicas: IP66 CRI>70. Acabado Dgclas. 6,6 kg Certificaciones: 2006/95/CE - Directiva Baja Tensión. 2004/108/CE - Directiva CEM. UNE-EN 60598: 2005 Luminarias. UNE-EN 62031: 2009 Módulos LED para alumbrado general. Requisitos de seguridad. UNE-EN 61347-2-13: 2007 Dispositivos de control de lámpara. UNE-EN 55015:2007 Límites y métodos de medida de las características relativas a la perturbación radioeléctrica de los equipos de iluminación y similares. UNE-EN 61547 Equipos para alumbrado de uso general. Requisitos de inmunidad - CEM. UNE-EN 61000-3-2 Compatibilidad electromagnética (CEM). UNE-EN 61000-3-3 Compatibilidad electromagnética (CEM).

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	49 W	CRI	80
Total flux	6420 lm	LOR	100%
Luminous efficacy	131 lm/W	Total power	49 W

Mounting mode

Ceiling mounted, Pole top mounted

Electric

System power: 49 W

Shape and measurements

Length: 21.65 in
Width: 10.63 in
Height: 6.10 in

Protection

IP: 65

Adjustability

Rotatable, Tilttable